

Safety data sheet

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2006/05/15
Version: 1.0

Page: 1/6
(30036523/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Molecular formula: (C₁₂H₁₂O₄)_n
Synonyms: Poly(butylene terephthalate)

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
30965-26-5	> 70.0 - < 90.0 %	polybutylene terephthalate (PBT)
65997-17-3	< 10.0 %	Glass, oxide, chemicals

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear NIOSH-certified chemical goggles.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Ingestion may cause gastrointestinal disturbances. Contact with molten product may cause thermal burns.

Irritation:

Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes.

Information on: Ultradur PBT

ULTRADUR PBT resin in pellet form is not expected to be hazardous.

Repeated dose toxicity:

Safety data sheet

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2006/05/15
Version: 1.0

Page: 2/6
(30036523/MDS_GEN_US/EN)

No known chronic effects.

Information on: Fiberglass

This product contains glass fibers which are compounded into the polymer matrix and thus are not expected to present the same hazards as fiberglass wool.

Information on: Fiberglass

Animal implantation studies have indicated that fiberglass wool is an animal carcinogen. A small study of Canadian glass wool workers reported a statistically significant increase in deaths due to lung cancer; however, animal inhalation studies and several large-scale studies of U.S. and European fiberglass wool workers have shown no statistically significant increases in lung cancer. The International Agency for Research on Cancer (IARC) has classified this material in Category 2B.

Information on: Fiberglass

These findings are based on glass wool, which has a smaller diameter than continuous glass filament or glass fiber chopped strands or rovings. Fiberglass wool is not used in this product.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Flash point:

No data available.

Autoignition:

350 °C

(ASTM D1929)

Suitable extinguishing media:

water, foam, dry extinguishing media

Hazards during fire-fighting:

carbon monoxide, tetrahydrofuran, can be emitted at > 290 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Safety data sheet

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2006/05/15
Version: 1.0

Page: 3/6
(30036523/MDS_GEN_US/EN)

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

General advice:

Keep container tightly closed.

8. Exposure controls and personal protection

Components with workplace control parameters

Glass, oxide, chemicals

ACGIH	TWA value 5 mg/m ³ Inhalable fraction ; TWA value 1 fibers/cm ³ Fiber ; TWA value 1 fibers/cm ³ Fiber ; TWA value 0.2 fibers/cm ³ Fiber ;
-------	---

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

General safety and hygiene measures:

Wash soiled clothing immediately.

9. Physical and chemical properties

Form:	granules
Odour:	odourless

Safety data sheet

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2006/05/15
Version: 1.0

Page: 4/6
(30036523/MDS_GEN_US/EN)

Colour:	various, depending on the colourant	
pH value:	No data available.	
melting range:	220 - 230 °C	(DIN 53736)
Density:	1.3 - 1.8 g/cm ³	(EN/ISO 1183-1)
Bulk density:	600 - 800 kg/m ³	
Solubility in water:	insoluble	

10. Stability and reactivity

Conditions to avoid:
> 290 degrees Celsius

Decomposition products:
Hazardous decomposition products: carbon monoxide, tetrahydrofuran

Thermal decomposition:
298 - 400 °C

11. Toxicological information

Chronic toxicity

Other information:
Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport

Biodegradation:
Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation:

The product will not be readily bioavailable due to its consistency and insolubility in water..

13. Disposal considerations

Waste disposal of substance:
Check for possible recycling.
May be disposed of or combusted with domestic refuse according to local regulations.

Container disposal:
Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport information

Safety data sheet

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2006/05/15
Version: 1.0

Page: 5/6
(30036523/MDS_GEN_US/EN)

Land transport *USDOT*

Not classified as a dangerous good under transport regulations

Sea transport *IMDG*

Not classified as a dangerous good under transport regulations

Air transport *IATA/ICAO*

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:
TSCA, US released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

State regulations

State RTK

CAS Number
65997-17-3

Chemical name
Glass, oxide, chemicals

State RTK
MA, NJ, PA

16. Other information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

Tech Desk
1-800-527-8324

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Corporation or BASF AG

Safety data sheet

ULTRADUR® B 4300 G2 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2006/05/15

Page: 6/6

Version: 1.0

(30036523/MDS_GEN_US/EN)

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET