

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 1/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

#### Recommended use of the chemical and restriction on use

Recommended use\*: Polymer; for industrial processing only

Suitable for use in industrial sector: Polymers industry

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: polyoxymethylene copolymerizate (POM)

Synonyms: POLYOXYMETHYLENE COPOLYMER

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

No need for classification according to GHS criteria for this product.

#### Label elements

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 2/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

The product does not require a hazard warning label in accordance with GHS criteria.

### Hazards not otherwise classified

#### Labeling of special preparations (GHS):

HEATING DURING PROCESSING OF PRODUCT MAY RESULT IN RELEASE OF THE DECOMPOSITION PRODUCT FORMALDEHYDE. This product is capable of releasing formaldehyde into the air. Contains formaldehyde. May cause cancer. UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

---

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Under the referenced regulation, this product does not contain any components classified for health hazards above the relevant cut off value.

---

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

If formaldehyde vapour is inhaled, remove person to fresh air and keep warm, if necessary summon physician. Inhale corticosteroid dose aerosol.

##### If on skin:

Burns caused by molten material require hospital treatment.

##### If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

##### If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention. Do not induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Symptoms: No significant reaction of the human body to the product known.

Hazards: No hazard is expected under intended use and appropriate handling.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Treat symptomatically.

---

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 3/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

---

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
water spray, foam, dry powder

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, Formaldehyde,

Formation of further decomposition and oxidation products depends upon the fire conditions. Under special fire conditions traces of other toxic substances are possible.

#### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

### 6. Accidental release measures

#### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

#### Personal precautions, protective equipment and emergency procedures

Wear suitable personal protective clothing and equipment.

#### Environmental precautions

No special precautions necessary. This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

#### Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up.

---

### 7. Handling and Storage

#### Precautions for safe handling

Provide suitable exhaust ventilation at the processing machines. Avoid inhalation of dusts/mists/vapours.

Protection against fire and explosion:

Containers should be grounded against electrostatic charge.

#### Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Carbon steel (Iron)

---

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 4/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

### 8. Exposure Controls/Personal Protection

No occupational exposure limits known.

#### Advice on system design:

Provide exhaust ventilation at sources when processing molten product.

#### Personal protective equipment

##### Respiratory protection:

Wear a NIOSH-certified organic vapour cartridge respirator when handling molten materials. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

##### Hand protection:

Chemical resistant protective gloves, Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

##### Eye protection:

Safety glasses with side-shields.

##### Body protection:

Body protection must be chosen based on level of activity and exposure.

##### General safety and hygiene measures:

Avoid inhalation of vapour. Wash soiled clothing immediately.

### 9. Physical and Chemical Properties

Form:	pellets	
Odour:	product specific	
Odour threshold:	No applicable information available.	
Colour:	various, depending on the colourant	
pH value:	not applicable	
melting range:	160 - 175 °C	(DIN EN ISO 3146)
Boiling range:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	320 - 340 °C	(ASTM D1929)
Flammability:	not self-igniting	
Flammability of Aerosol Products:	not applicable, the product does not form flammable aerosoles	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	320 - 340 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	1.4 g/cm <sup>3</sup> ( 20 °C)	(DIN 53479)
Relative density:	Study does not need to be conducted.	
Bulk density:	850 kg/m <sup>3</sup>	
Vapour density:	not applicable	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 5/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

Self-ignition temperature:	not self-igniting
Thermal decomposition:	> 240 °C To avoid thermal decomposition, do not overheat. May decompose violently. Gaseous products of degradation can be given off if the product is greatly overheated.
Viscosity, dynamic:	not applicable, the product is a solid
Viscosity, kinematic:	not applicable, the product is a solid
Solubility in water:	insoluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	The product is a non-volatile solid.

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

Do not process with PVC or other plastics containing halogenated flame retardants.

#### Conditions to avoid

Temperature: > 240 degrees Celsius

#### Incompatible materials

inorganic acids, organic acids

#### Hazardous decomposition products

Decomposition products:

Possible decomposition products: carbon monoxide, Formaldehyde, carbon dioxide, Water

Thermal decomposition:

> 240 °C

To avoid thermal decomposition, do not overheat. May decompose violently. Gaseous products of degradation can be given off if the product is greatly overheated.

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 6/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

### Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

### *Information on: Formaldehyde*

*Assessment of acute toxicity: Of high toxicity after short-term inhalation. Of high toxicity after single ingestion. Of pronounced toxicity after short-term skin contact.*

### Oral

Type of value: ATE

Value: > 5,000 mg/kg

### Inhalation

The inhalation of fumes represents a severe acute hazard. Irritating to respiratory system.

### Dermal

Type of value: ATE

Value: > 5,000 mg/kg

### Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

The product has not been tested. The statement has been derived from the properties of the individual components.

### Irritation / corrosion

Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

### *Information on: Formaldehyde*

*Assessment of irritating effects: Corrosive! Damages skin and eyes. Depending on the concentration and duration of exposure, aqueous solutions can cause a strongly irritating or corrosive effect on the skin or eyes.*

### Sensitization

#### *Information on: Formaldehyde*

*Assessment of sensitization:*

*Caused skin sensitization in animal studies. Caused sensitization in humans.*

*OSHA (Occupational Safety and Health Administration) has classified this substance as a skin sensitizer. OSHA (Occupational Safety and Health Administration) has classified this substance as a respiratory sensitizer.*

### Aspiration Hazard

No aspiration hazard expected.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 7/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

### Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Carcinogenicity

Assessment of carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### *Information on: Formaldehyde*

*Assessment of carcinogenicity: NTP listed carcinogen The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to occurrence of nasopharyngeal cancer and leukemia. Current regulatory information is provided in this MSDS. No adverse health effects are anticipated if recommended personal protective equipment and industrial hygiene practices are used.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

## **Symptoms of Exposure**

No significant reaction of the human body to the product known.

### Medical conditions aggravated by overexposure

The use of products that contain or liberate formaldehyde is regulated under the OSHA Formaldehyde Standard (see 29 CFR 1910.1048).

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

### **Persistence and degradability**

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

### **Bioaccumulative potential**

#### Bioaccumulation potential

# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 8/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

The product will not be readily bioavailable due to its consistency and insolubility in water.

---

### 13. Disposal considerations

**Waste disposal of substance:**

Check for possible recycling. Incinerate in suitable incineration plant, observing local authority regulations.

**Container disposal:**

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

---

### 14. Transport Information

**Land transport**

USDOT

Not classified as a dangerous good under transport regulations

**Sea transport**

IMDG

Not classified as a dangerous good under transport regulations

**Air transport**

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

**Federal Regulations**

**Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

**Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:**

Based on BASF Corporation's knowledge of the product composition and manufacturing process, exposure to this product is not expected to contain substances subject to prior warning under California Proposition 65 regulations. Since BASF does not expect California Proposition 65 listed substances to be present, we do not routinely analyze this product for these substances.

**WARNING:** For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

[Other Prop 65 components may be present in the product.]

**NFPA Hazard codes:**

Health: 2 Fire: 1 Reactivity: 0 Special:



# Safety Data Sheet

## ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL

Revision date : 2017/11/27

Page: 9/9

Version: 4.0

(30192031/SDS\_GEN\_US/EN)

### HMIS III rating

Health: 2      Flammability: 1      Physical hazard: 0

---

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2017/11/27

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

ULTRAFORM® W2320 003 UNCOLORED Q600 POLYACETAL is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET