

Safety data sheet

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE

Revision date : 2009/02/05

Page: 1/6

Version: 1.2

(30277598/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company

BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Chemical family: polyamide

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25038-54-4	>= 60.0 - <= 80.0 %	polyamide (PA 6)
65997-17-3	>= 20.0 - <= 40.0 %	Glass, oxide, chemicals
1333-86-4	< 1.0 %	carbon black

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

Potential health effects**Primary routes of exposure**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns.

Irritation:

Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes.

Sensitization:

No data available concerning sensitizing effects. provisional classification.

Repeated dose toxicity:

No known chronic effects.

Safety data sheet

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE

Revision date : 2009/02/05

Page: 2/6

Version: 1.2

(30277598/MDS_GEN_US/EN)

Information on: Fiberglass

This product contains glass fibers which are compounded into the polymer matrix and thus are not expected to present the same hazards as fiberglass wool.

Information on: Fiberglass

Animal implantation studies have indicated that fiberglass wool is an animal carcinogen. A small study of Canadian glass wool workers reported a statistically significant increase in deaths due to lung cancer; however, animal inhalation studies and several large-scale studies of U.S. and European fiberglass wool workers have shown no statistically significant increases in lung cancer. The International Agency for Research on Cancer (IARC) has classified this material in Category 2B.

Information on: Fiberglass

These findings are based on glass wool, which has a smaller diameter than continuous glass filament or glass fiber chopped strands or rovings. Fiberglass wool is not used in this product.

Potential environmental effects

Aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Assist in breathing if necessary. Keep patient calm, remove to fresh air. Consult a physician.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

If irritation develops, seek medical attention. In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Flash point:	> 400 °C	(Unspecified)
Autoignition:	> 400 °C	(ASTM D1929)
Self-ignition temperature:		not self-igniting

Suitable extinguishing media:

water, foam, dry extinguishing media, carbon dioxide

Hazards during fire-fighting:

No particular hazards known.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Safety data sheet

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE

Revision date : 2009/02/05

Page: 3/6

Version: 1.2

(30277598/MDS_GEN_US/EN)

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

Reclaim for processing if possible. Sweep/shovel up. Place into suitable containers for reuse or disposal in a licensed facility.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

Protection against fire and explosion:

No explosion proofing necessary.

Storage

General advice:

Keep container tightly closed. Avoid deposition of dust.

Storage stability:

Protect against moisture.

8. Exposure controls and personal protection

Components with workplace control parameters

Glass, oxide, chemicals

	ACGIH	TWA value 5 mg/m3 Inhalable fraction ; TWA value 1 fibers/cm ³ Fiber ; TWA value 1 fibers/cm ³ Fiber ; TWA value 0.2 fibers/cm ³ Fiber ;
carbon black	OSHA	PEL 3.5 mg/m3 ;
	ACGIH	TWA value 3.5 mg/m3 ;

Advice on system design:

Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

Safety data sheet

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE

Revision date : 2009/02/05

Page: 4/6

Version: 1.2

(30277598/MDS_GEN_US/EN)

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust.

9. Physical and chemical properties

Form:	granules	
Odour:	odourless	
Colour:	various, depending on the colourant	
pH value:		not applicable
Melting temperature:	approx. 220 °C	(DIN 53765)
Boiling range:		The substance / product decomposes therefore not determined.
Vapour pressure:		not applicable
Density:	1.10 - 1.60 g/cm ³	(20 °C) (EN ISO 1183-1)
Bulk density:	500 - 800 kg/m ³	
Solubility in water:		insoluble

10. Stability and reactivity

Decomposition products:

Hazardous decomposition products: carbon monoxide, hydrogen cyanide

Thermal decomposition:

> 300 °C

11. Toxicological information

Chronic toxicity

Genetic toxicity:

No data available concerning mutagenic effects. provisional classification.

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation:

The product will not be readily bioavailable due to its consistency and insolubility in water.

Safety data sheet

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE

Revision date : 2009/02/05

Page: 5/6

Version: 1.2

(30277598/MDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling.
Dispose of in a licensed facility.
Observe all local regulations.

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

State regulations

State RTK

CAS Number

65997-17-3
1333-86-4

Chemical name

Glass, oxide, chemicals
carbon black

State RTK

MA, NJ, PA
MA, NJ, PA

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

Safety data sheet

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE

Revision date : 2009/02/05

Page: 6/6

Version: 1.2

(30277598/MDS_GEN_US/EN)

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

Tech Desk
800 5278324

ULTRAMID® B3WG6 CR BLACK 23210 POLYAMIDE is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET