

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 1/9
(30278671/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Recommended use of the chemical and restriction on use

Recommended use*: Polymer; for industrial processing only
Suitable for use in industrial sector: Polymers industry

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms: Polybutylene(terephthalate)

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 2/9
(30278671/SDS_GEN_US/EN)

The product does not require a hazard warning label in accordance with GHS criteria.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

Contains an IARC Group 2B carcinogen - possibly carcinogenic to humans.

CAUTION:

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear NIOSH-certified chemical goggles.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
1333-86-4	>= 0.1 - < 1.0 %	carbon black

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
30965-26-5	>= 40.0 - <= 60.0 %	polybutylene terephthalate (PBT)
26062-94-2	>= 40.0 - <= 60.0 %	polybutylene terephthalate (PBT)
27812-34-6	>= 3.0 - <= 70.0 %	Styrene-acrylonitrile-maleic anhydride copolymer
1333-86-4	>= 0.1 - < 1.0 %	carbon black

4. First-Aid Measures

Description of first aid measures

General advice:

Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Wash thoroughly with soap and water. Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 3/9
(30278671/SDS_GEN_US/EN)

If swallowed:

Rinse mouth and then drink plenty of water. Ingestion is not likely in the available physical form. If ingested, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: No significant reaction of the human body to the product known.
Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat symptomatically.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon monoxide, tetrahydrofuran, can be emitted at > 290 °C
Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

Environmental precautions

No special precautions necessary.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.
For large amounts: Pick up with suitable appliance and dispose of.

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 4/9
(30278671/SDS_GEN_US/EN)

7. Handling and Storage

Precautions for safe handling

Avoid inhalation of dusts/mists/vapours.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Stainless steel, aluminum

Further information on storage conditions: Keep container tightly closed. Avoid deposition of dust. Protect against moisture.

Storage stability:

Protect against moisture.

8. Exposure Controls/Personal Protection

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Wear respiratory protection if ventilation is inadequate. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust.

9. Physical and Chemical Properties

Form:	pellets	
Odour:	odourless	
Odour threshold:		not applicable
Colour:	various, depending on	the colourant
pH value:		not applicable
melting range:	220 - 230 °C	(DIN 53736)

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 5/9
(30278671/SDS_GEN_US/EN)

Boiling range:		The substance / product decomposes therefore not determined.
Sublimation point:		No applicable information available.
Flash point:		No applicable information available.
Flammability:	not self-igniting	
Flammability of Aerosol Products:		not applicable, the product does not form flammable aerosoles)
Lower explosion limit:		The substance / product decomposes therefore not determined.
Upper explosion limit:		The substance / product decomposes therefore not determined.
Autoignition:	350 °C	(ASTM D1929)
Vapour pressure:		not applicable
Density:	1.3 - 1.8 g/cm3	(20 °C) (EN ISO 1183-1)
Relative density:		No data available.
Bulk density:	600 - 900 kg/m3	
Vapour density:		not applicable
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Self-ignition temperature:		not self-igniting
Thermal decomposition:	> 290 °C	Thermal decomposition above the indicated temperature is possible.
Viscosity, dynamic:		not applicable, the product is a solid
Viscosity, kinematic:		not applicable, the product is a solid
Solubility in water:		insoluble
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		The product is a non-volatile solid.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is chemically stable.

No hazardous reactions known.

Conditions to avoid

Temperature: > 290 degrees Celsius

Incompatible materials

No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, tetrahydrofuran, terephthalic acid, carbon dioxide, Water

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 6/9
(30278671/SDS_GEN_US/EN)

Thermal decomposition:

> 290 °C

Thermal decomposition above the indicated temperature is possible.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Inhalation

Not inhalable due to the physico-chemical properties of the product.

Dermal

Type of value: ATE

Value: > 5,000 mg/kg

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization

Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 7/9
(30278671/SDS_GEN_US/EN)

Assessment of carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Information on: carbon black

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.

Reproductive toxicity

Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Symptoms of Exposure

No significant reaction of the human body to the product known.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Bioaccumulative potential

Bioaccumulation potential

The product will not be readily bioavailable due to its consistency and insolubility in water.

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling. Incinerate in suitable incineration plant, observing local authority regulations.

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 8/9
(30278671/SDS_GEN_US/EN)

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Not hazardous;

State regulations

State RTK

MA, NJ, PA

CAS Number

1333-86-4

Chemical name

carbon black

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

NFPA Hazard codes:

Health : 1 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2015/01/12

Safety Data Sheet

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE

Revision date : 2015/01/12
Version: 1.0

Page: 9/9
(30278671/SDS_GEN_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ULTRADUR® B 4560 BLACK 10089 POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET