

## Safety Data Sheet

# ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 1/10  
(30613498/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

#### Recommended use of the chemical and restriction on use

Recommended use\*: Polymer; for industrial processing only  
Suitable for use in industrial sector: Polymers industry

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: polyester  
Synonyms: Polybutylene terephthalate

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

No need for classification according to GHS criteria for this product.

#### Label elements

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 2/10  
(30613498/SDS\_GEN\_US/EN)

The product does not require a hazard warning label in accordance with GHS criteria.

### Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

## 3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
25068-38-6	>= 1.0 - < 3.0%	bisphenol A-epichlorohydrin resin
25038-59-9	>= 15.0 - < 20.0%	Polyethyleneterephthalate (PET)
1333-86-4	>= 1.0 - < 3.0%	carbon black

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

#### If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

#### If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

#### If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

#### If swallowed:

Rinse mouth and then drink plenty of water. Ingestion is not likely in the available physical form. If ingested, seek medical attention. Do not induce vomiting.

### Most important symptoms and effects, both acute and delayed

Symptoms: No significant reaction of the human body to the product known.

Hazards: No hazard is expected under intended use and appropriate handling.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat symptomatically.

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 3/10  
(30613498/SDS\_GEN\_US/EN)

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
water spray, foam, dry powder, carbon dioxide

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon monoxide, tetrahydrofuran, can be emitted at > 290 °C  
Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

#### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### 6. Accidental release measures

#### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

#### Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

#### Environmental precautions

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

#### Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.  
For large amounts: Pick up with suitable appliance and dispose of.  
Reclaim for processing if possible. Place into suitable containers for reuse or disposal in a licensed facility.

### 7. Handling and Storage

#### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid inhalation of dusts/mists/vapours. Provide good ventilation of working area (local exhaust ventilation if necessary).

#### Protection against fire and explosion:

The product is capable of dust explosion. Take precautionary measures against static discharges.

#### Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 4/10  
(30613498/SDS\_GEN\_US/EN)

Further information on storage conditions: Keep container tightly closed. Avoid deposition of dust.  
Protect against moisture.

Storage stability:  
Protect against moisture.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

carbon black	OSHA PEL ACGIH TLV	PEL 3.5 mg/m <sup>3</sup> ; TWA value 3.5 mg/m <sup>3</sup> ; TWA value 3 mg/m <sup>3</sup> Inhalable fraction ;
Glass, oxide, chemicals	ACGIH TLV	TWA value 5 mg/m <sup>3</sup> Inhalable fraction ; TWA value 1 fibers/cm <sup>3</sup> Fiber ; Respirable fibers: length > 5 micrometers; aspect ratio >= 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.

#### **Advice on system design:**

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

#### Personal protective equipment

##### **Respiratory protection:**

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

##### **Hand protection:**

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

##### **Eye protection:**

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles).

##### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

##### **General safety and hygiene measures:**

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions.  
Avoid inhalation of dust. Wash soiled clothing immediately.

### 9. Physical and Chemical Properties

Form:	pellets
Odour:	odourless
Odour threshold:	not applicable
Colour:	black
pH value:	not applicable
Melting point:	245 °C

(DIN 53736)

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 5/10  
(30613498/SDS\_GEN\_US/EN)

Boiling range:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	> 400 °C	
Flammability:	not self-igniting	
Flammability of Aerosol Products:	not applicable, the product does not form flammable aerosoles	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	350 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	1.3 - 1.8 g/cm3 ( 20 °C)	(EN ISO 1183-1)
Relative density:	Study does not need to be conducted.	
Bulk density:	600 - 900 kg/m3	(DIN 53466)
Vapour density:	not applicable	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 300 °C May decompose if overheated and/or subjected to prolonged heating.	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	
Solubility in water:	insoluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	The product is a non-volatile solid.	

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:  
not fire-propagating

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is chemically stable.  
No hazardous reactions known.

#### Conditions to avoid

Temperature: > 290 degrees Celsius

#### Incompatible materials

No substances known that should be avoided.

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 6/10  
(30613498/SDS\_GEN\_US/EN)

### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, tetrahydrofuran, terephthalic acid, carbon dioxide, Water

Thermal decomposition:

> 300 °C

May decompose if overheated and/or subjected to prolonged heating.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

#### Oral

Type of value: ATE

Value: > 5,000 mg/kg

#### Inhalation

Not inhalable due to the physico-chemical properties of the product.

#### Dermal

Type of value: ATE

Value: > 5,000 mg/kg

#### Assessment other acute effects

No applicable information available.

#### Irritation / corrosion

Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

#### Sensitization

Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Aspiration Hazard

No aspiration hazard expected.

### Chronic Toxicity/Effects

#### Repeated dose toxicity

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 7/10  
(30613498/SDS\_GEN\_US/EN)

Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Carcinogenicity

Assessment of carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### *Information on: carbon black*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

## **Symptoms of Exposure**

No significant reaction of the human body to the product known.

### Medical conditions aggravated by overexposure

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product. See MSDS section 11 - Toxicological information.

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

#### Aquatic toxicity

*Information on: Glass, oxide, chemicals*

*Assessment of aquatic toxicity:*

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 8/10  
(30613498/SDS\_GEN\_US/EN)

*There is a high probability that the product is not acutely harmful to aquatic organisms. Based on long-term (chronic) toxicity study data, the product is very likely not harmful to aquatic organisms.*

-----

### Persistence and degradability

#### Assessment biodegradation and elimination (H2O)

Experience shows this product to be inert and non-degradable.

### Bioaccumulative potential

#### Bioaccumulation potential

The product will not be readily bioavailable due to its consistency and insolubility in water.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Incinerate in a licensed facility. Do not discharge substance/product into sewer system.

### **Container disposal:**

Dispose of in accordance with national, state and local regulations.

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

---

## 14. Transport Information

### **Land transport**

USDOT

Not classified as a dangerous good under transport regulations

### **Sea transport**

IMDG

Not classified as a dangerous good under transport regulations

### **Air transport**

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

## 15. Regulatory Information

### **Federal Regulations**

#### **Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

### **State regulations**



# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 9/10  
(30613498/SDS\_GEN\_US/EN)

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	1333-86-4	carbon black
	65997-17-3	Glass, oxide, chemicals
PA	14807-96-6	talc
	1333-86-4	carbon black
	65997-17-3	Glass, oxide, chemicals

### Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

**WARNING:** This product can expose you to chemicals including CARBON BLACK (AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE [ $\leq 10$  MICROMETERS]) which is known to the State of California to cause cancer, and METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

[Other Prop 65 components may be present in the product.]

### NFPA Hazard codes:

Health: 1      Fire: 1      Reactivity: 0      Special:

### HMIS III rating

Health: 1      Flammability: 1      Physical hazard: 0

---

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2017/10/02

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO

# Safety Data Sheet

## ULTRADUR® B4040G6 HR BLACK 15029 POLYBUTYLENE TEREPHTHALATE

Revision date : 2017/10/02  
Version: 5.0

Page: 10/10  
(30613498/SDS\_GEN\_US/EN)

---

OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION  
GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET